

Cleaner F3 10 Litre 62555

- Universal, pH neutral cleaner for the pre-commission cleaning of new and existing HVAC and light commercial heating systems
- Specially formulated to remove market leading fluxes, oils, greases, iron oxides and other system debris quickly and efficiently
- Recommended to be left in the system for up to one week under operating conditions
- Inhibited cleaner designed to protect the system during cleaning
- Contains fast-acting dispersant technology which is suitable in all types of system water: hard, soft, artificially softened and demineralised water
- Non-foaming formula which is easy to remove from the system after use, saving time on-site



A universal cleaner designed for use in HVAC and light commercial heating and cooling systems, Cleaner F3 can be used for the pre-commission cleaning of new systems, removing flux residues, oil/grease and other installation debris. Cleaner F3 can also be used to remove sludge, scale and other circulating debris in existing contaminated systems, therefore improving efficiency and avoiding damage to system components. This high performance, fast-acting cleaner is compatible with all metals and materials commonly used in heating and cooling systems, including steel and aluminium. One 10 litre product treats up to a 2000 litre system at a dose rate of 0.5%.

Application

For optimum results, the entire system should be completely drainable. Cleaner F3 should be dosed at a concentration of 0.5%. The product can be introduced into the system via a suitable point such as a dosing pot. For pre-commission cleaning, circulate Cleaner F3 in the system for at least one hour at normal operating temperature. To remove sludge from existing systems, circulate under normal operating conditions, for up to 7 days until acceptable flow around the system has been achieved. Additional/ repeat applications of Cleaner F3 may be necessary if systems are heavily sludged. Drain and flush with cold water until the water is clear and the Cleaner F3 has been rinsed from the system. Finally, add an appropriate Fernox inhibitor such as Protector F1 to prevent further corrosion damage and scale deposits.

Specification

Colour: Amber
 Odour: Faintly aromatic
 Form: Liquid
 pH (conc): 6.6
 pH (in-use) 6.5 - 7.7
 SG: 1.116 @ 20°C

Package, Handling & Safety

Fernox Cleaner F3 is supplied in 10 litre containers. Fernox Cleaner F3 is classified as non-hazardous, but as with all chemicals: Keep out of reach of children. Do not mix with other chemicals. In case of contact with eyes or skin, rinse immediately with plenty of water.

Single Item

Height mm	310
Width mm	230
Depth mm	205
Weight kg	12.000
Barcode EAN	5014551625556

Outer Carton

Outer Height mm	310
Outer Width mm	230
Outer Depth mm	205
Outer Weight kg	12.000
Transit Type	Euro 1200 x 800
Cartons per layer	20
Layers per transit type	2

Last modification 15-11-2021 (d/m/y)